

LED Wraparound

The DuraGem LED Wraparound, 4-FT, 130 lm/W, Damp Location, Dimmable + Smart Ready

FEATURES

Lumen Output	2860 to 5200 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
Size	4-FT
CCT	4000K or 5000K
Rating	Damp Location
Warranty	7 Years

APPLICATIONS

Premium indoor luminaire suitable for general indoors, lobbies, offices, meeting rooms, restrooms, hallways, stairwells, storage-closets, kitchens, and work-stations.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Suitable for Dry and Damp Locations.

ELECTRICAL

Input voltage 120-277V models with 0-10V Continuous Dimming. Operating temperatures -4°F to 122°F (-20°C to 50°C).

MOUNTING

Surface Mounting on ceilings or beams.

OPTICS

Anti-UV Prismatic Frosted Polycarbonate Lens.

EMERGENCY

Installed 90 Minute Emergency Backup Battery LED Driver available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

7 year exclusive limited warranty. View complete product warranty information <https://etheriumled.com/warranty/>.


Project:
Date:
Catalog No:
Prepared By:

4-FT Models




CORRELATED COLOR TEMPERATURES (CCT)

4000K



5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 22W, 40W
Power Factor: >0.9
Total Harmonic Distortion (THD): <10%
Operating Temperature: -4°F to 122°F (-20°C to 50°C)

LIGHTING DATA

Lumens: 2860, 5200
Lumens Per Watt: 130 lm/W
Color Correlated Temperature (CCT): 4000K, 5000K
Dimmable: 0-10V
Color Rendering Index (CRI): >82
L70: 75000 hours

ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions	Weight
ETH-WRP-4-22W-4K	4-FT	22W	120-277V	0.18A@120V, 0.08A@277V	2860	130 lm/W	4000K	0-10V	White	47.75"L x 7.12"W x 2.80"H	7.40 lbs
ETH-WRP-4-22W-5K	4-FT	22W	120-277V	0.18A@120V, 0.08A@277V	2860	130 lm/W	5000K	0-10V	White	47.75"L x 7.12"W x 2.80"H	7.40 lbs
ETH-WRP-4-40W-4K	4-FT	40W	120-277V	0.33A@120V, 0.14A@277V	5200	130 lm/W	4000K	0-10V	White	47.75"L x 7.12"W x 2.80"H	7.20 lbs
ETH-WRP-4-40W-5K	4-FT	40W	120-277V	0.33A@120V, 0.14A@277V	5200	130 lm/W	5000K	0-10V	White	47.75"L x 7.12"W x 2.80"H	7.20 lbs

Emergency

EM	INSTALLED - 90 Minute Emergency Backup Battery LED Driver
(Blank)	None

ORDERING GUIDE

ETH	WRP	4	22W	4K	EM
ETH	Group	Size	Wattage	CCT	Emergency

PHYSICAL DIMENSIONS

All Models

47.75"L x 7.12"W x 2.80"H



SHIPPING INFORMATION

Model Wattage	Unit Weight	Inner Carton Dimensions	Inner Carton Weight	Qty /Box	Master Carton Dimensions	Master Carton Weight	Qty /Box
22W	7.40 lbs	48.63"L x 7.50"W x 3.00"D	8.49 lbs	1	49.13"L x 13.00"W x 8.00"D	36.20 lbs	4
40W	7.20 lbs	48.63"L x 7.50"W x 3.00"D	8.49 lbs	1	49.13"L x 13.00"W x 8.00"D	36.20 lbs	4



ETH-WRP-4-22W-XK

