SATCO NUVO

Project Name

Prepared By



SATCO S13150

72W/LED/HID-HB/840/120-277V/DI

Notes

General	
Status	Active
Watts	72W
Volts	120V-277V
Shape	N/A
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	82
Lumens	11000L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	HID
Technology	LED
Min Compartment Size	Diameter: 11.81 in. Height: 13.78 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Fraguency	50/60 Hz
Operating Frequency Burning Position	Vertical with Base Up
Dulling i Osition	Vertical With Dase Op
	Ruilt-in surge protection - 6KV
Surge Protection	Built-in surge protection - 6KV
	Built-in surge protection - 6KV -40C (-40F) to a maximum of +60C (+140F)
Surge Protection	-40C (-40F) to a maximum of +60C
Surge Protection Operating Temperature	-40C (-40F) to a maximum of +60C
Surge Protection Operating Temperature Physical	-40C (-40F) to a maximum of +60C (+140F)
Surge Protection Operating Temperature Physical MOL	-40C (-40F) to a maximum of +60C (+140F)
Surge Protection Operating Temperature Physical MOL MOD	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34
Surge Protection Operating Temperature Physical MOL MOD Lens Finish	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09 Yes 5 Year Limited - Hi-Pro
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09 Yes 5 Year Limited - Hi-Pro
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09 Yes 5 Year Limited - Hi-Pro cULus Classified; cULus Listed Damp
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09 Yes 5 Year Limited - Hi-Pro cULus Classified; cULus Listed Damp No
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star California Status	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09 Yes 5 Year Limited - Hi-Pro cULus Classified; cULus Listed Damp No Lawful for sale
Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star California Status RoHS Compliant	-40C (-40F) to a maximum of +60C (+140F) 8.15 6.34 Clear Glass White 2.09 Yes 5 Year Limited - Hi-Pro cULus Classified; cULus Listed Damp No Lawful for sale Yes







