

Notes

www] 09-27-2021 00:19:1

| General | |
|--------------------------------|---|
| Status | Active |
| Watts | 8W |
| Incandescent Equivalent | 110W |
| Fluorescent Equivalent | 17W/15W |
| Ballast Type | Туре А |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 24.00 |
| Finish | Gloss White |
| CCT (Kelvin) | 3500 |
| Temperature | Neutral White |
| CRI | 82 |
| Lumens | 1250L |
| Beam Spread | 210 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |
| | |
| Electrical | |
| Operating Frequency | 50/60 Hz |
| Power Factor | 0.9 |
| THD | 20% |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |
| Physical | |
| MOL | 23.78 |
| MOD | 1.1 |
| Material | Glass |
| Lens Finish | Gloss White |
| Lens Material | Glass |
| Housing Color | White |
| Weight (lb.) | 0.24 |
| Additional Information | |
| Tube Guard Use | Approved for use with tube guards when operated on Low or Normal ballast factor systems |
| Warranty | 5 Year Limited - T8 LED Bulbs |
| Compliance | |
| | cULus |
| Safety Listing Location Rating | |
| - | Damp |
| Energy Star | No Var |
| DLC Approved | Yes |
| DLC ID | PLFWYWU1CBAG |
| California Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |

For More Information Visit: http://www.satco.com/







