SATCO" NUVO"

Project Name

Location

Prepared By

SATCO S8890

13T8/LED/48-830/DUAL/BP-DR

Notes

[www] 10-11-2021 02:06:33

Status	Activo
Status	Active
Watts	13W
Fluorescent Equivalent	28W/32W
Volts	120V-277V
Ballast Type	
Shape -	
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48.00
Finish	Frost
CCT (Kelvin)	3000
Temperature	Warm White
CRI	83
Lumens	1800L
Beam Spread	240
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast required (Type A) or Balla Bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.96
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
Physical	
MOL	47.78
MOD	1
Material	Glass
Lens Finish	Frost
Housing Color	White
Additional Information	
Additional Info	Do not use with dimmers in by- pass mode. Check the ballast for dimming capability when using wi a ballast.
Shatter-Proof Type	PET Coated
Specification Note	Ballast Compatible - bare lamp is 12W; Ballast Bypass - 13W.; Protection from arcing- Power mu be turned off prior to installing lamps. Sockets must be in good working order, not broken, cracke or electrically compromised. If arcing occurs at the lamp pin, thermal fuse may activate to avoi overheating of lamp.
	ovonioating of lamp.
Warranty	5 Year Limited - T8 LED Bulbs
-	5 Year Limited - T8 LED Bulbs
Warranty Compliance	5 Year Limited - T8 LED Bulbs cULus Listed for Type A; cULus

Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PL20BPLJYLDH
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes

Copyright 2020 Satco Products, Inc. All Rights Reserved

For More Information Visit: <u>http://www.satco.com/</u>

